SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: CLEANER Product Code: PLUDET1000

1.2 Relevant identified uses of the mixture and uses advised against.

PVC CLEANER Uses advised against: Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	POLYPIPE ITALIA SRL
Address:	Loc. Pianmercato 5c-5d-5h
City:	Monleone di Cicagna
Province:	Genova GF
Telephone:	+39 0185 929399
E-mail:	
Web:	info@polypipeitalia.com www.polypipeitalia.com

1.4 Emergency Phone: 0039 0185 929399 Toxicology Information Service (National Institute of Toxicology and Forensic Sciences) Phone: +39 02 66101029 Only for the purposes of providing health response in

emergencies.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008: Eye Irrit. 2 : Causes serious eye irritation. Flam. Liq. 2 : Highly flammable liquid and vapour. STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EU)	No 1272/2008:
Pictograms:	



Signal Word:

Danger

n statements.	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
P statements:	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take precautionary measures against static discharge.
P271	Use only outdoors or in a well-ventilated area.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P305+P351+F	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and
easy to do. Co	ntinue rinsing.

- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P501 Dispose of contents/container to an authorized point of treatment.

EUH statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

(in accordance with Regulation (EU) No

453/2010)

Version: 0 Revision date: 29/07/2015

Page 2 of 11 Print date: 29/07/2015

2.3 Other hazards.

The product may have the following additional risks: Do not ingest

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	specific concentration limit
Index No: 606-001- 00-8 CAS No: 67-64-1 EC No: 200-662-2 Registration No: 01- 2119471330-49-XXXX	[1] acetone,propan-2-one,propanone	>= 50% < 75 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 606-002- 00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01- 2119457290-43-XXXX	[1] butanone,ethyl methyl ketone	>= 50% < 75 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a Community workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

If wearing contact lenses, remove them. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious

Page 3 of 11 Print date: 29/07/2015

SECTION 5: FIREFIGHTING MEASURES.

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. Avoid breathing fumes.For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks.For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away

(in accordance with Regulation (EU) No

453/2010)

Version: 0 Revision date: 29/07/2015

Page 4 of 11 Print date: 29/07/2015

oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Degreasing cleaner for PVC pipes

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
		Deutschland	Eight hours	500	1200
		[1]	Short term	1000	2400
		Econica [2]	Eight hours	500	1210
		España [2]	Short term		
		European	Eight hours	500	1210
		Union [3]	Short term		
acatana propan 2 ana propanana	67-64-1	Franco [4]	Eight hours	500	1210
acetone,propan-2-one,propanone	07-04-1	France [4]	Short term	1000	2420
		United	Eight hours	500	1210
		Kingdom [5]	Short term	1500	3620
		Dortugal [6]	Eight hours	500	1187
		Portugal [6]	Short term	750	1781
		Svorigo [7]	Eight hours	250	600
	Sverige [/	Sverige [7]	Short term	500	1200
		Deutschland	Eight hours	200	600
		[1]	Short term	800	2400
		España [2]	Eight hours	200	600
		Lspana [2]	Short term	300	900
		European	Eight hours	200	600
		Union [3]	Short term	300	900
butanone, ethyl methyl ketone	78-93-3	France [4]	Eight hours	200	600
butanone, eury methy ketone	70-95-5	Fiance [4]	Short term	300	900
		United	Eight hours	200	600
		Kingdom [5]	Short term	300	899
		Portugal [6]	Eight hours	200	590
		Portugal [6]	Short term	300	885
		Sverige [7]	Eight hours	50	150
		Sverige [7]	Short term	100	300

Biological exposure limit values for:

Name	CAS No.	Country	Biological indicator	BLV	Sampling time
acetone,propan-2-one,propanone	67-64-1	España [2]	Acetona en orina	50 mg/l	Final de la jornada laboral
butanone, ethyl methyl ketone	78-93-3	España [2]	Metiletilcetona en orina	2 mg/l	Final de la jornada laboral

[1] Laut Grenzwerte in der Luft am Arbeitsplatz "Luftgrenzwerte" verabschiedet vom Bundesminister für Arbeit und Sozialordnung im Bundesarbeitsblatt.

[2] Según la lista de Valores Límite Ambientales de Exposición Profesional adoptados por el Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT) para el año 2014.

[3] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[4] Selon la liste de Valeurs limites d'exposition professionnelle aux agents chimiques en France adoptés par Institut national de la recherche scientifique.

[5] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.

[6] De acordo com Português Padrão 1796 adotou pelo Instituto português de qualidade.

Page 5 of 11 Print date: 29/07/2015

[7] According Occupational Exposure Limit Values and Measures against Air Contaminants adopted by Swedish Work Environment Authority.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	1210 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	200 (mg/m ³)
acetone,propan-2-one,propanone N. CAS: 67-64-1 N. CE: 200-662-2	DNEL (Workers)	Inhalation, Acute, Local effects	2420 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	186 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	62 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	62 (mg/kg bw/day)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	600 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
hutanana athul mathul katana	DNEL (Workers)	Dermal, Long-term, Systemic effects	1161 (mg/kg bw/day)
butanone,ethyl methyl ketone N. CAS: 78-93-3 N. CE: 201-159-0	DNEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	31 (mg/kg bw/day)
	DMEL (General population)	Inhalation, Long-term, Systemic effects	106 (mg/m ³)
	DMEL (General population)	Dermal, Long-term, Systemic effects	412 (mg/m3)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
	aqua (freshwater)	10,6 (mg/L)
	aqua (marine water)	1,06 (mg/L)
	aqua (intermittent releases)	21 (mg/L)
acatana propan 2 ana propanana	PNEC STP	100 (mg/L)
acetone,propan-2-one,propanone N. CAS: 67-64-1	sediment (freshwater)	30,04 (mg/kg
N. CAS. 07-04-1 N. CE: 200-662-2		sediment dw)
N. CE. 200-002-2	sediment (marine water)	3,04 (mg/kg
		sediment dw)
	PNEC soil	29,5 (mg/kg
		soil dw)
	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg
		soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
butanone, ethyl methyl ketone	PNEC STP	709 (mg/L)
N. CAS: 78-93-3	sediment (freshwater)	284,74
N. CE: 201-159-0		(mg/kg
		sediment dw)
	sediment (marine water)	284,7 (mg/kg
		sediment dw)
	oral (Hazard for predators)	1000 (mg/kg
		food)

Version: 0 Revision date: 29/07/2015

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	PLUDET1000
Breathing protect	ion:
If the recommended	technical measures are observed, no individual protection equipment is necessary.
Hand protection:	
PPE:	Protective gloves.
Characteristics:	«CE» marking, category II.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight.
Observations:	Always use with clean, dry hands.
Material:	PVC (polyvinyl chloride) Breakthrough time > 480 Material thickness (mm): 0,35
Eye protection:	
If the product is han	dled correctly, no individual protection equipment is necessary.
Skin protection:	
PPE:	Anti-static protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance: Observations:	The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different
	widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance:Transparent liquid with characteristic odour Colour: Colorless Odour:Characteristic Odour threshold:N.A./N.A. pH:N.A./N.A. Melting point: N.A./N.A. Boiling Point: -80 °C Flash point: -15 °C Evaporation rate: N.A./N.A. Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: 167,33 Vapour density:N.A./N.A.

(in accordance with Regulation (EU) No 453/2010)

Version: 0 Revision date: 29/07/2015

Page 7 of 11 Print date: 29/07/2015

Relative density:0.81 g/cm³ Solubility:Prácticamente insoluble Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A. Partition coefficient (n-octanol/water): N.A./N.A. Auto-ignition temperature: N.A./N.A. Decomposition temperature: >300°C Viscosity: N.A./N.A. Explosive properties: N.A./N.A. Oxidizing properties: N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2. Other information.

VOC content (p/p): 100 % VOC content: **810** g/l

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

At high temperatures can occur pyrolysis and dehydrogenation.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.

10.5 Incompatible materials.

- Avoid the following materials:
- Acids.
- Bases.
- Oxidizing agents.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity; Not conclusive data for classification.

b) skin corrosion/irritation; Not conclusive data for classification.

c) serious eye damage/irritation; Product classified: Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation; Not conclusive data for classification.

(in accordance with Regulation (EU) No 453/2010)

Version: 0 Revision date: 29/07/2015

POLYPIPE ITALIA SRL

Page 8 of 11 Print date: 29/07/2015

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure;Product classified:Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity				
Name	Туре	Test	Kind	Value	
	Fish	LC50 Fish 3220 (mg/l) [1] [1] Brooke, L.T., D.J. Call, D.L. Geiger, and C.E. Northcott 1984. Acute Toxicities of Organic Chemicals to Fathead Minnows (Pimephales promelas), Vol. 1. Center for Lake Superior Environmental Stud., Univ.of Wisconsin-Superior, Superior, WI :414			
butanone,ethyl methyl ketone	Aquatic invertebrates	Specific Or		5090 (mg/l) [1] op 1980. Detoxification of Wet Oxidation. J.Water 2130	
CAS No: 78-93-3 EC No: 201-159-0	Aquatic plants	CE50	Desmodesmus subspicatus	>100 (mg/L)	

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
butanone, ethyl methyl ke	tone	0,29	_	_	Very low
N. CAS: 78-93-3	EC No: 201-159-0	0,29	-	-	very IOW

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

SAFETY DATA SHEET (in accordance with Regulation (EU) No

(In accordance with Regulation (EU) No 453/2010)

Version: 0 Revision date: 29/07/2015

Page 9 of 11 Print date: 29/07/2015

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions Sea: Transport by ship: IMDG. Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number.

UN No: UN1993

14.2 UN proper shipping name.

Description: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS BUTANONE, ETHYL METHYL KETONE), 3, PG II, (D/E)

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: II

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 33 ADR LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code.

The product is not transported in bulk.

Revision date: 29/07/2015

POLYPIPE ITALIA SRL

Page 10 of 11 Print date: 29/07/2015

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

See annex I of the Directive 96/82/EC of 9 December 1996 on the control of major-accident hazards involving dangerous substances and the Regulation (EC) No 689/2008 of the european parliament and of the council of 17 June 2008 concerning the export and import of dangerous chemicals and its subsequent updates.

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Labelling in accordance with Directive 1999/45/EC:

Symbols:



Highly flammable

R Phrases:

R Phrases:	
R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
S Phrases:	
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S24	Avoid contact with skin.
S33	Take precautionary measures against static discharges.
S40	To clean the floor and all objects contaminated by this material, use (to be specified by the manufacturer).
S43	In case of fire, use (indicate in the space the precise type of fire-fighting equipment. If water increases
risk, add «Never use water»).	
S51	Use only in well-ventilated areas.


Irritant

(in accordance with Regulation (EU) No 453/2010)

Version: 0 Revision date: 29/07/2015

POLYPIPE ITALIA SRL

Page 11 of 11 Print date: 29/07/2015



Health hazard: 1 (Slightly Hazardous) Flammability: 4 (Below 73°F)

Reactivity: 0 (Stable)

Abbreviations and acronyms used:

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be
- considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- Log Pow: Logarithm of the partition octanol-water.
- NOEC: No observed effect concentration.
- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) No 453/2010. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.