



COMERCIAL QUÍMICA MASSÓ, S.A.  
Česká Republika  
Baarova 1542/48 14000 PRAHA 4  
Tel.: 420 241006571 Fax: 420 241481798

# TRS HARDENER 1000 E

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : TRS HARDENER 1000 E

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : Hardener (Crosslinker)  
Function or use category : Absorbents and adsorbents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Comercial Química Massó, S.A. (Česká Republika)  
Baarova 1542/48  
140 00 Praha 4 - CESHÁ REPUBLIKA  
T +420 241 006 571 - F +420 241 481 798  
[msds.support@cqmasso.com](mailto:msds.support@cqmasso.com)

#### 1.4. Emergency telephone number

Emergency number : 704 100 087 (España)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H225  
Category 2  
Acute toxicity H332  
(inhalation:dust,mist)  
Category 4  
Skin corrosion/irritation, H315  
Category 2  
Serious eye damage/eye H319  
irritation, Category 2  
Respiratory sensitisation, H334  
Category 1  
Skin sensitisation, Category H317  
1  
Carcinogenicity, Category 2 H351  
Specific target organ toxicity H335  
— Single exposure,  
Category 3, Respiratory  
tract irritation  
Specific target organ toxicity H336  
— Single exposure,  
Category 3, Narcosis  
Specific target organ toxicity H373  
— Repeated exposure,  
Category 2

Full text of H statements : see section 16

#### Adverse physicochemical, human health and environmental effects

No additional information available



Date of issue: 22/10/2018  
Revision date: 15/10/2018  
Version: 1.1  
Supersedes: 24/08/2017

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Extra labelling to display/Extra classification(s) to display

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

ethyl acetate; 4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate; 4-isocyanatosulphonyltoluene; tosyl isocyanate; Diphenylmethane Diisocyanate, isomers and homologues

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H332 - Harmful if inhaled.  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP) :

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P405 - Store locked up.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P241 - Use explosion-proof equipment.

PPP safety precautions :

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethyl acetate	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5 (REACH-no) 01-2119475103-46	50 - 100	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (EC Index-No.) 615-005-00-9 (REACH-no) 01-2119457014-47	25 - 50	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317

Diphenylmethane Diisocyanate, isomers and homologues	(CAS-No.) 9016-87-9 (EC-No.) POLYMER	10 - 20	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
4-isocyanatosulphonyltoluene; tosyl isocyanate	(CAS-No.) 4083-64-1 (EC-No.) 223-810-8 (EC Index-No.) 615-012-00-7 (REACH-no) 01-2119980050-47	0,1 - 1	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (EC Index-No.) 615-005-00-9 (REACH-no) 01-2119457014-47	(C >= 0,1) Resp. Sens. 1, H334 (C >= 5) Eye Irrit. 2, H319 (C >= 5) Skin Irrit. 2, H315 (C >= 5) STOT SE 3, H335
4-isocyanatosulphonyltoluene; tosyl isocyanate	(CAS-No.) 4083-64-1 (EC-No.) 223-810-8 (EC Index-No.) 615-012-00-7 (REACH-no) 01-2119980050-47	(C >= 5) Skin Irrit. 2, H315 (C >= 5) STOT SE 3, H335 (C >= 5) Eye Irrit. 2, H319

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Suspected of causing cancer.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

See Heading 1.2.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

ethyl acetate (141-78-6)		
France	Local name	Acétate d'éthyle
France	VME (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
France	VME (ppm)	400 ppm
Germany	TRGS 900 Local name	Ethylacetat
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	1500 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	400 ppm
Germany	TRGS 900 Remark	DFG,Y
Portugal	Local name	Acetato de etilo
Portugal	OEL TWA (ppm)	400 ppm
Spain	Local name	Acetato de etilo
Spain	VLA-ED (mg/m <sup>3</sup> )	1460 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	400 ppm
United Kingdom	Local name	Ethyl acetate

ethyl acetate (141-78-6)		
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (ppm)	400 ppm
Switzerland	Local name	Acétate d'éthyle
Switzerland	MAK (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	400 ppm
Switzerland	KZGW (mg/m <sup>3</sup> )	2800 mg/m <sup>3</sup>
Switzerland	KZGW (ppm)	800 ppm
Switzerland	Remark (CH)	4x15
4,4'-methylenediphenyl diisocyanate; diphenylmethane-4,4'-diisocyanate (101-68-8)		
France	Local name	4,4'-Diisocyanate de diphenylméthane
France	VME (mg/m <sup>3</sup> )	0,1 mg/m <sup>3</sup>
France	VME (ppm)	0,01 ppm
France	VLE (mg/m <sup>3</sup> )	0,2 mg/m <sup>3</sup>
France	VLE (ppm)	0,02 ppm
France	Note (FR)	Valeurs recommandées/admises; certaines ou toutes ces VLE s'entendent pour des concentrations mesurées sur une durée de 5 min; risque d'allergie respiratoire, substance classée cancérigène de catégorie 2
Germany	TRGS 900 Local name	4,4'-Methylenediphenyldiisocyanat
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	0,05 mg/m <sup>3</sup> (E)
Germany	TRGS 900 Remark	DFG;11;12;H;Sah;Y
Portugal	Local name	Metilendifenilisocianato (MDI)
Portugal	OEL TWA (ppm)	0,005 ppm
Spain	Local name	Diisocianato de 4,4'-difenilmetano (MDI)
Spain	VLA-ED (mg/m <sup>3</sup> )	0,052 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	0,005 ppm
Spain	Notes	Sen (Sensibilizante), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) n° 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Diphenylmethane Diisocyanate, isomers and homologues (9016-87-9)		
Germany	TRGS 900 Local name	pMDI (als MDI berechnet)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	0,05 mg/m <sup>3</sup> (E)
Germany	TRGS 900 Remark	DFG;H;Sah;Y;12

### 8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection	: Chemical resistant gloves according to EN 374. The gloves are recommended with a protection factor 6; corresponding > 480 minutes of permeation time. For example nitrile rubber (0.4 mm), neoprene rubber (0.5 mm), chlorure de polivinilo (0.7 mm). The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemical which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as the instructions/specifications provided by the gloves supplier.
Eye protection	: Chemical goggles or safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Combined filter for organic, inorganic gases, inorganic acids and alkaline / steam type ABEK (according to EN 14387)
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 70 °C
Flash point	: < 23 °C
Auto-ignition temperature	: ≈ 460 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 0,987 g/ml
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: ≈ 14 Pa.s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Harmful if inhaled.

ATE CLP (dust,mist)	4,323 mg/l/4h
---------------------	---------------

#### ethyl acetate (141-78-6)

LD50 oral rat	≈ 4934 mg/kg
---------------	--------------

LD50 dermal rabbit	> 20 ml/kg
--------------------	------------

LC50 inhalation rat (mg/l)	≈ 200 mg/l/4h
----------------------------	---------------

#### 4-isocyanatosulphonyltoluene; tosyl isocyanate (4083-64-1)

LD50 oral rat	≈ 2234 mg/kg
---------------	--------------

#### Diphenylmethane Diisocyanate, isomers and homologues (9016-87-9)

LD50 oral rat	> 15000 mg/kg
---------------	---------------

LC50 inhalation rat (Vapours - mg/l/4h)	≈ 490 mg/l/4h
---	---------------

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Suspected of causing cancer.  
 Reproductive toxicity : Not classified  
 STOT-single exposure : May cause respiratory irritation. May cause drowsiness or dizziness.  
 STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  
 Aspiration hazard : Not classified

#### TRS HARDENER 1000 E

Viscosity, kinematic	≈ 14184,397 mm <sup>2</sup> /s
----------------------	--------------------------------

Potential adverse human health effects and symptoms : Harmful if inhaled.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Diphenylmethane Diisocyanate, isomers and homologues (9016-87-9)

LC50 fishes	> 100 mg/l
-------------	------------

EC50 Daphnia	> 100 mg/l
--------------	------------

ErC50 (algae)	> 100 mg/l
---------------	------------

### 12.2. Persistence and degradability

#### TRS HARDENER 1000 E

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### TRS HARDENER 1000 E

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods




Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA
<b>14.1. UN number</b>		
1993	1993	1993
<b>14.2. UN proper shipping name</b>		
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.
<b>Transport document description</b>		
UN 1993 FLAMMABLE LIQUID, N.O.S. (ethyl acetate), 3, II, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, II	UN 1993 Flammable liquid, n.o.s., 3, II
<b>14.3. Transport hazard class(es)</b>		
3	3	3
		
<b>14.4. Packing group</b>		
II	II	II
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : F1  
 Special provisions (ADR) : 274, 601, 640D  
 Limited quantities (ADR) : 11  
 Excepted quantities (ADR) : E2  
 Packing instructions (ADR) : P001, IBC02, R001  
 Mixed packing provisions (ADR) : MP19  
 Portable tank and bulk container instructions (ADR) : T7  
 Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28  
 Tank code (ADR) : LGBF  
 Vehicle for tank carriage : FL  
 Transport category (ADR) : 2  
 Special provisions for carriage - Operation (ADR) : S2, S20  
 Hazard identification number (Kemler No.) : 33



Orange plates : 

Tunnel restriction code (ADR) : D/E

### - Transport by sea

Special provisions (IMDG) : 274  
Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T7  
Tank special provisions (IMDG) : TP1, TP8, TP28  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : B

### - Air transport

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3H

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions  
Contains no substance on the REACH candidate list  
Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

Ensure all national/local regulations are observed.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes:

General update.

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : workers must have risk-specific training.

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	On basis of test data
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 2	H373	Calculation method

The information in this document is based on our best current knowledge. No part of its contents should be considered as a warranty, express or implied, to specific properties and / or product use conditions. In all cases, it is the responsibility of users matching the recommendations and determining the suitability of any product for a particular application or use. For this and other reasons, we assume no liability for loss, damage or expense caused by matters relating to the handling, storage, use or disposal of product.